



01 October 2009

UPM Raflatac Sheetstock Marketing

## FSC Certified Coloured Vellum range

Dear Partner Merchant,

Following environmental market needs and looking for a better service and higher added value products, UPM Raflatac launches the new FSC certified coloured Vellum range. This new solution will replace the existing coloured Vellum grades.

As per new grades we're also looking for a renewed shades, with more vivid and intense colours, meanwhile the same main technical properties remain on similar level,

Change in the range is forecasted to take effect during 4Q'2009, and it will be carried out gradually as our old stocks run out.

Old product	New FSC range	Adhesive	Sales code	Sheet size (cm)	W0 no score no backprint EAN code	W2 score, no backprint EAN code
Vellum Yellow (D4)	Vellum Yellow F cert MC (BEP)	Permanent Greentac Plus (SP34)	BEPS3414	50 x 70	7113586	7113593
Vellum Green (D7)	Vellum Green F cert MC (BER)	Permanent Greentac Plus (SP34)	BERS3414	50 x 70	7113609	7113616
Vellum Blue (DH)	Vellum Blue F cert MC (BES)	Permanent Greentac Plus (SP34)	BESS3414	50 x 70	7113623	7113630
Vellum Red (DM)	Vellum Red F cert MC (BET)	Permanent Greentac Plus (SP34)	BETS3414	50 x 70	7113647	7113579

The updated product range and technical information sheets are also available in our web.

*We kindly ask you to forward this information to the persons concerned in your organization.*

Best Regards

UPM Raflatac Sheetstock Sales and Marketing

FSC (Forest Stewardship Council) is an international non-governmental organisation founded in 1993, whose task is to support environmentally appropriate, socially beneficial, and economically viable management of the world's forests. Forests certified against FSC standards are located in more than 60 countries. The Council has defined ten general principles of forest management. The actual certification standards are drawn up in accordance with the FSC principles in a national cooperation process. Fulfilling the FSC standard requires independent third-party verification. More information: [www.fsc.org](http://www.fsc.org).

01 October 2009

UPM Raflatac Sheetstock Marketing

**UPM RAFLATAC  
TECHNICAL INFORMATION**

**SELF- ADHESIVE  
FACE  
UNCOATED PAPER**  
**Product**  
**Use**

01/09/2009

SHEETS

VELLUM YELLOW F cert MC

BEP

Woodfree pulp dyed SC paper

Eye catching display labels for price marking and promotional use.  
Information labels printed on ink-jet, lasers and copiers.

**Typical technical values**

<b>Substance</b>	80	g/m <sup>2</sup>	ISO 536	
<b>Caliper</b>	100	µm	ISO 534	
<b>Tensile strength MD</b>	5,0	kN/m	ISO 1924/1	
<b>Tensile strength CD</b>	3,3	kN/m	ISO 1924/1	
<b>Roughness</b>	2,4	microns	ISO 8791	PPS 10
<b>Printability</b>	Offset, flexography, letterpress, ink-jet, lasers and copiers.			
<b>Additional info</b>	Products named as F cert are registered to FSC SGS-COC-004879			

**Warranty**

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot take responsibility for any damage caused through their use.

This technical sheet replaces all previous versions. All information is subject to change without notice.

01 October 2009

UPM Raflatac Sheetstock Marketing

**UPM RAFLATAC  
TECHNICAL INFORMATION**

<b>SELF- ADHESIVE</b>	01/09/2009
<b>FACE</b>	SHEETS
<b>UNCOATED PAPER</b>	<b>VELLUM GREEN F cert MC</b>
<b>Product</b>	BER
<b>Use</b>	Woodfree pulp dyed SC paper Eye catching display labels for price marking and promotional use. Information labels printed on ink-jet, lasers and copiers.

**Typical technical values**

<b>Substance</b>	80	g/m <sup>2</sup>	ISO 536
<b>Caliper</b>	100	µm	ISO 534
<b>Tensile strength MD</b>	5,0	kN/m	ISO 1924/1
<b>Tensile strength CD</b>	3,3	kN/m	ISO 1924/1
<b>Roughness</b>	2,4	microns	ISO 8791 PPS 10
<b>Printability</b>	Offset, flexography, letterpress, ink-jet, lasers and copiers.		
<b>Additional info</b>	Products named as F cert are registered to FSC SGS-COC-004879		

Warranty

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot take responsibility for any damage caused through their use.

This technical sheet replaces all previous versions. All information is subject to change without notice.

01 October 2009

UPM Raflatac Sheetstock Marketing

**UPM RAFLATAC  
TECHNICAL INFORMATION**

<p><b>SELF- ADHESIVE FACE UNCOATED PAPER</b></p> <p><b>Product Use</b></p>	<p>01/09/2009 RLO SHEETS <b>VELLUM BLUE F cert MC BES</b> Woodfree pulp dyed SC paper Eye catching display labels for price marking and promotional use. Information labels printed on ink-jet, lasers and copiers.</p>
--	---

**Typical technical values**

<p><b>Substance</b></p> <p><b>Caliper</b></p> <p><b>Tensile strength MD</b></p> <p><b>Tensile strength CD</b></p> <p><b>Roughness</b></p> <p><b>Printability</b></p> <p><b>Additional info</b></p>	<p>80      g/m<sup>2</sup>      ISO 536</p> <p>100     µm            ISO 534</p> <p>5,0      kN/m        ISO 1924/1</p> <p>3,3      kN/m        ISO 1924/1</p> <p>2,4      microns     ISO 8791      PPS 10</p> <p>Offset, flexography, letterpress, ink-jet, lasers and copiers.</p> <p>Products named as F cert are registered to FSC SGS-COC-004879</p>
--	--

**Warranty**

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot take responsibility for any damage caused through their use.

This technical sheet replaces all previous versions. All information is subject to change without notice.

01 October 2009

UPM Raflatac Sheetstock Marketing

**UPM RAFLATAC  
TECHNICAL INFORMATION**

<p><b>SELF- ADHESIVE FACE UNCOATED PAPER</b></p> <p><b>Product Use</b></p>	<p>01/09/2009 SHEETS <b>VELLUM RED F cert MC</b> BET</p> <p>Woodfree pulp dyed SC paper Eye catching display labels for price marking and promotional use. Information labels printed on ink-jet, lasers and copiers.</p>
--	---

**Typical technical values**

<p><b>Substance</b></p> <p><b>Caliper</b></p> <p><b>Tensile strength MD</b></p> <p><b>Tensile strength CD</b></p> <p><b>Roughness</b></p> <p><b>Printability</b></p> <p><b>Additional info</b></p>	<p>80      g/m<sup>2</sup>      ISO 536</p> <p>100     μm            ISO 534</p> <p>5,0      kN/m          ISO 1924/1</p> <p>3,3      kN/m          ISO 1924/1</p> <p>5,5      microns      ISO 8791      PPS 10</p> <p>Offset, flexography, letterpress, ink-jet, lasers and copiers.</p> <p>Products named as F cert are registered to FSC SGS-COC-004879</p>
--	---

**Warranty**

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot take responsibility for any damage caused through their use.

This technical sheet replaces all previous versions. All information is subject to change without notice.