



Castgloss FSC Certified

Sustainable business from premium sustainable labelling

The new FSC Certified Castgloss meets market demand for environmentally responsible labelling that satisfies the highest quality standards. It also improves over the original Castgloss with higher weight, whiteness and brightness.

Combined with our standard sheet adhesives, Castgloss F Cert MC is suitable for a wide range of end-uses requiring an excellent high-gloss foundation for premium-quality print work.

- FSC certified from sustainably managed forests
- Higher whiteness and brightness.
- 84 gr/m², mirror-like gloss for highest quality labels

The new solution will replace the existing Castgloss grades. Change in the range is forecasted to take effect from April 2011, and it will be carried out gradually as our old stocks run out.

EAN code	Sales code	Combination	Sheet size
7120034	BWF SP34 14 W3	Castgloss F Cert MC / SP 34 / Kraft Special 90	64 x 45
7120126	BWF SP34 14 W0	Castgloss F Cert MC / SP 34 / Kraft Special 90	50 x 70
7120089	BWF SP34 14 W1	Castgloss F Cert MC / SP 34 / Kraft Special 90	50 x 70
7120041	BWF SP34 14 W3	Castgloss F Cert MC / SP 34 / Kraft Special 90	50 x 70
7120096	BWF SP34 14 W1	Castgloss F Cert MC / SP 34 / Kraft Special 90	100 x 70
7120058	BWF SP34 14 W3	Castgloss F Cert MC / SP 34 / Kraft Special 90	100 x 70
7120102	BWF SP3H 14 W1	Castgloss F Cert MC / SP 3H / Kraft Special 90	50 x 70
7120065	BWF SP3H 14 W3	Castgloss F Cert MC / SP 3H / Kraft Special 90	50 x 70
7120119	BWF SP3H 14 W1	Castgloss F Cert MC / SP 3H / Kraft Special 90	100 x 70
7120072	BWF SR21 14 W3	Castgloss F Cert MC / SR 21 / Kraft Special 90	50 x 70
7120133	BWF SP3H 2Y W0	Castgloss F Cert MC / SP 34 / White Kraft 180	50 x 70

UPM RAFLATAC TECHNICAL INFORMATION

03/2011 ENG

SELF-ADHESIVE	SHEETS
FACE	CASTGLOSS F cert MC
Gloss Coated	BWF (sales code)
Product	Cast-coated, wood-free paper with mirror-like gloss finish.
Use	For high quality multicolour, glossy product labels.

Typical technical values

Substance	84	g/m ²	ISO 536	
Caliper	86	µm	ISO 534	
Tensile strength MD	5.3	kN/m	ISO 1924/1	
Tensile strength CD	3.1	kN/m	ISO 1924/1	
Brightness	93	%	ISO 2470/1	
Roughness	0,5	microns	ISO 8791	PPS 10
Gloss	90	%	Hunter 75°	
Opacity	90	%	ISO 2471	
Whiteness	130	%	ISO 11475	

Printability Flexography, letterpress, rotogravure, offset, screen and hot foil.

Approvals Products named as F cert MC are registered to SGS-COC-004879 FSC™ mixed credit.

Warranty Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use.

This publication replaces all previous versions. All information is subject to change without notice.

