



SR 29

New removable adhesive for Sheet filmic applications

The new SR29 is specially developed for Sheets filmic applications where longterm removability and good clarity and UV-Stability are needed. This phthalates free acrylic water based adhesive is suitable for toy labelling and childcare articles according to EU Directive 2005/84/EC.

SR29 will replace our SR28, the change will be carried out gradually as our old stocks run out.

EAN code	Sales Code	Combination	Sheet size
7124476	WESR2935W1	PE White Offset / SR29 / White Kraft 130/ W1	50x70
7124483	WESR2935W1	PE White Offset / SR29 / White Kraft 130/ W1	100x70

UPM RAFLATAC TECHNICAL INFORMATION

14/06/2010

ADHESIVE SR29

REMOVABLE SR29 (sales code)

Type Removable adhesive for synthetic materials for sheets

Composition Acrylic dispersion

Use With synthetic materials, SR29 has longterm removability, good clarity and UV-stability. Suitable for labelling toys and childcare articles according to EU Directive 2005/84/EC.

Typical technical values

Tack min	3	N	FTM9	
Tack max	8	N	FTM9	
Shear min	8	h	FTM8	
Peel min	1,5	N/25mm	FTM2	90°
Labelling temperature min	5	°C		
Service temperature min	-10	°C		
Service temperature max	80	°C		

Limitations Limited adhesion on very rough surfaces

Shelf life From the date of manufacture: 2 years at +20 °C and RH 50%.

Warranty Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use.

This publication replaces all previous versions. All information is subject to change without notice.



UPM